

本公司於出廠前已添加潤滑油脂(BT-860-0)，在正常條件下運轉20,000小時可不必更換潤滑油脂，但在特殊環境條件下運轉時，如：高溫、長時間運轉、衝擊負荷等，則換油頻率為10,000-15,000小時。

ALL REDUCERS FILLED WITH LUBRICANT(BT-860-0)BEFORE DELIVERY, NORMALLY, IT NO NEED TO REPLACE LUBRICANT FOR FIRST 20,000 HRS RUNNING, BUT IF WORKING IN SPECIAL APPLICATION, SUCH AS: HIGH TEMPERATURE, 24 HRS RUNNING, HEAVY DUTY IMPACT....etc. THEN LUBRICANT NEED TO BE CHANGED IN EVERY 10,000-15,000 WORKING HOURS.

可替換潤滑油脂 (EXCHANGEABLE LUBRICANT)

廠牌 (BRAND)	SHELL	COSMD	MOBIL	昭和石油	台製
規格 (SPEC)	OMALA OIL 320	EP-320	MOBIL GEAR 632	ISO VG EP 320	國光牌 HD-320

油量表/重量表 (LUBRICANT / WEIGHT TABLE)

馬力 CAPACITY	出力軸 OUTPUT SHAFT	本體框號 HOUSING CODE	機型TYPE								
			油量表 (公升) LUBRICANT(L)		重量表 (公斤) WEIGHT(KG)						
			CH CHM CHD	CV CVM CVD	CH	CHM	CHD	CV	CVM	CVD	
100W	φ18	1#	0.19	0.18	5.60	5.22	2.90	5.80	5.12	2.80	
	φ22	2#	0.38	0.39	7.30	6.40	4.00	7.30	6.52	4.10	
1/8HP	φ28	1#+3#	0.8	0.85	14.6	12.4	11.3	14.6	12.52	11.4	
200W	φ18	1#	0.17	0.18	7.00	5.22	2.90	7.00	5.12	2.80	
	φ22	2#	0.38	0.39	8.60	6.42	4.00	8.80	6.52	4.10	
	φ28	3#	0.63	0.68	11.0	9.12	8.30	10.8	8.92	8.10	
1/4HP	φ32	2#+4#	1.30	1.40	27.6	24.0	23.0	28.0	24.4	22.8	
400W	φ22	2#	0.38	0.39	11.1	6.42	4.80	11.2	6.52	4.90	
	φ28	3#	0.63	0.68	14.2	9.12	8.30	14.0	8.92	8.10	
	φ32	4#	0.95	1.05	27.0	22.2	21.5	26.9	23.2	22.5	
1/2HP	φ40	3#+5#	1.80	1.90	46.0	39.8	39.1	47.0	40.8	40.1	
750W	φ28	3#	0.63	0.68	15.5	12.1	8.30	15.0	11.9	8.10	
	φ32	4#	0.95	1.05	27.6	25.1	21.5	28.0	26.1	22.5	
	φ40	5#	1.26	1.38	42.3	37.3	32.0	41.9	36.3	31.0	
1HP	φ50	3#+6#	3.00	3.13	91.5	83.5	79.2	91.5	82.5	77.2	
	φ32	4#	0.95	1.05	33.6	25.0	22.0	34.6	26.0	23.0	
	1500W	φ40	5#	T	1.470	1.590	49.6	37.3	33.0	49.0	36.3
TT				1.260	1.470						
2HP	φ50	6#	2.520	2.600	94.0	74.3	70.0	94.0	71.3	67.0	
	φ50	4#+6#	3.470	3.650	105.0	--	--	106.0	--	--	
2200W 3HP	φ40	5#	D	1.680	1.800	49.8	40.8	36.5	51.0	39.8	35.5
			T	1.490	1.590						
	φ50	6#	2.520	2.600	92.5	77.8	73.5	88.5	74.8	70.5	
3700W 5HP	φ40	5#	1.680	1.800	54.8	43.8	39.5	55.3	42.8	38.5	
	φ50	6#	2.520	2.600	98.5	78.8	74.5	94.5	75.8	71.5	

備註：1. 此表僅供參考，具體以實物為準

1. THIS TABLE IS FOR REFERENCE ONLY, SUBJECT TO THE SPECIFIC KIND