

三相電壓全負載電流值 3-PHASE/4-POLES FULL LOAD AMPERE

輸出馬力 CAPACITY	50HZ-4P					60HZ				
	220V	380V	415V	440V	RPM	220V	380V	440V	460V	RPM
100W	0.60	0.40	0.32	0.30	1410	0.6	0.35	0.30	0.29	1720
200W	1.15	0.67	0.61	0.58	1410	1.1	0.63	0.55	0.52	1720
400W	2.14	1.24	1.13	1.07	1420	1.9	1.10	0.95	0.91	1730
750W	3.67	2.13	1.94	1.84	1420	3.4	1.96	1.70	1.63	1730
1500W	6.59	3.82	3.49	3.30	1430	6.1	3.53	3.05	2.92	1740
2200W	8.94	5.18	4.74	4.47	1430	8.7	5.04	4.35	4.16	1740
3700W	13.85	8.03	7.34	6.93	1440	13.5	7.82	6.75	6.46	1745

單相電壓全負載電流值 1-PHASE/4-POLES FULL LOAD AMPERE

輸出馬力 CAPACITY	50HZ-4P			60HZ-4P		
	110V	220V	RPM	110V	220V	RPM
100 W	4.00	2.00	1410	3.80	1.90	1720
200 W	5.00	2.50	1410	4.60	2.30	1720
400 W	8.40	4.20	1420	7.80	3.90	1730
750 W	14.20	7.10	1420	12.90	6.40	1730
1500 W	26.00	13.00	1430	23.40	11.70	1740

單相馬達電容器規格 1-PHASE MOTOR CAPACITOR

輸出馬力 CAPACITY	運轉電容(文電型) RUNNING CAPACITOR (NON-CENTRIFUGAL TYPE)	起動電容(離心開關型) STARTING CAPACITOR (THE CENTRIFUGAL SWITCH TYPE)	運轉電容 + 起動電容 (離心開關型) RUNNING & STATING (THE CENTRIFUGAL SWITCH TYPE)
100 W	10 μ f-450v	----	-----
200 W	16 μ f-450v	125 μ f-250v	-----
400 W	30 μ f-450v	----	30 μ f-450v+200 μ f-250v
750 W	35 μ f-450v	----	35 μ f-450v+300 μ f-250v
1500W	-----	----	50 μ f-450v+400 μ f-250v

項目ITEM	三相交流馬達3-PHASE MOTOR		單相交流馬達1-PHASE MOTOR	
保護等級 PROTECTION	全密閉外扇型IP-54 TOTALLY ENCLOSED FAN COOLED TYPE		半密閉外扇型 SEMI-ENCLOSECD FAN COOLED TYPE	
外殼材質 HOUSING MATERIAL	0.1-3.7KW	鋁合金 ALUM ALLOY	0.1-1.5KW	鐵殼 STEEL PLATE
	0.1-3.7KW	鐵殼 STEEL PLATE	0.1-1.5KW (OPTIONAL)	鋁合金 ALUM ALLOY
啓動方式 STARTING	全壓啓動 DIRECT START		0.1-0.2KW	運轉電容啓動 CAPACITOR
			0.4-1.5KW	起動電容啓動+離心開關 Capacitor & centrifugal switch
定格 TIME RATING	連續運轉 CONTINUOUS RUNNING		連續運轉 CONTINUOUS RUNNING	
絕緣等級 INSULATION	F-絕緣 F-CLASS		F-絕緣 F-CLASS	
適用環境 ENVIRONMENT	溫度：-10°C TO +40°C (TEMPERATURE BETWEEN -10°C AND +40°C) 濕度：90%以下 (HUMIDITY LESS THAN 90%)			
適用電壓 VOLTAGE	50HZ	220V,230V,240V,380V, 400V,415V,440V	50HZ	110V,115V,200V, 220V,230V
	60HZ	220V,240V,380V,415V, 440V,460V,480V,600V	60HZ	110V,220V,240V
適用極數 POLE	2P,4P,6P,8P		4P	
輸出轉數(4P) FULL SPEED	50HZ	1360-1430RPM	50HZ	1340-1400RPM
	60HZ	1640-1740RPM	60HZ	1610-1720RPM
依據標準 STANDARD	國際/國家標準 IEC-34,CNS-10919 ACCORDING TO IEC-34,CNS-10919			
海拔 SEA LEVEL	1000公尺以下 UNDER 1000M			
接線盒 TERMINAL BOX	採用IP55級防水型鋁合金接線盒 WITH IP-55 CLASS WATER-PROOF ALUMINUM TERMINAL BOX			